

2600 Dryslinger II

For Cargo Hook Equipped Helicopters



Optional Equipment

- **Low Flow Orifice and Gate:** For materials such as grass seed and herbicides where low flow rates are required.
- **Bucket Cover:** Instant access vinyl and nylon bucket cover with transparent hatch.
- **Slurry Option:** Bucket configured for a wet slurry application system.
- **Auger Option:** Internal auger system for constant flow regardless of product.
- **Load Bag:** Allows bucket to be refilled in seconds for large scale operations.



Standard Models

- **2600-20G:** Capacity 20 cubic feet, Net Wt. 120 lbs., 5.5HP gas motor
- **2600-20H:** Capacity 20 cubic feet, Net Wt. 90 lbs., hydraulic motor
- **2600-25G:** Capacity 25 cubic feet, Net Wt. 220 lbs., 13.5HP gas motor
- **2600-25H:** Capacity 25 cubic feet, Net Wt. 190 lbs., hydraulic motor
- **2600-45G:** Capacity 45 cubic feet, Net Wt. 260 lbs., 13.5 gas motor
- **2600-45H:** Capacity 45 cubic feet, Net Wt. 230 lbs., hydraulic motor
- **2600-85G:** Capacity 85 cubic feet, Net Wt. 560 lbs., 27HP gasoline*
- **2600-85H:** Capacity 85 cubic feet, Net Wt. 490 lbs., hydraulic motor
- **2600-Custom:** Custom buckets with capacities over 100 cubic feet

**Now offering 28 HP EFI Gasoline Engines*

Specifications

- **Flow Rate:** adjustable rate ranging from .5 to 300 pounds per acre.
- **Cyclic Control:** allows for complete pilot control of unit.
- **Open Spinner:** eliminates clogging, spreads product accurately.
- **Directional Fins:** prevents rotation or spinning of bucket during flight.